

NEW!



PRINETO Velcro under-floor heating system

For fast and practical laying by one person

Quick and easy – the **PRINETO** Velcro system pays off

The **PRINETO** Velcro surface heating system stands out on account of its especially easy and quick installation: The **PRINETO** ECO-flex Velcro surface heating pipe green-linked has Velcro strip wound spirally around it so that it can be laid in no time on the specially laminated **PRINETO** Velcro insulation board. The flexible pipe is simply unrolled as usually and laid on the Velcro system roll without the use of tools. The Velcro strip on the pipe engages automatically with the backing foil on the insulation board and provides an optimum and secure hold.

A 5/10 cm laying grid printed onto the backing foil of the Velcro system roll is used as an orientation aid. The **PRINETO** Velcro surface heating pipe is unrolled with the aid of the **PRINETO** pipe reel carrier and fixed in place easily by foot on the insulation at the pre-calculated spacing pattern – going easy on the fitter's back and without any special laying or fixing tools being necessary. Corrections can always be carried out easily.

Thanks to the water-impermeable Velcro backing foil and its self-adhesive foil overlap, the **PRINETO** Velcro system is suitable both for cement screed and wet-laid screed.

The **PRINETO** Velcro surface heating system at a glance:

- Fast and simple laying – without any tools being necessary
- Installation time reduced by up to 30 % thanks to direct bonding of the insulation boards and convenient pipe fixing
- Efficiency increased by up to 50 % through one-man laying
- Ultra-flexible self-cross-linking ECO-flex surface heating pipe, green-linked – ideal even for rooms with nooks and crannies
- Rigid MLCP Velcro surface heating pipe – ideal for the installation of wall-panel heating



A perfectly matched system

PRINETO Velcro surface heating pipe



The ultra-flexible **PRINETO** ECO-flexsurface heating pipe green-linked is made of self-cross-linking PE-HDS of the dimension 17x2.

It is oxygen-tight according in line with DIN 4724 and, thanks to its Velcro hook strip, can be laid on the **PRINETO** Velcro insulation board (system roll) quickly and without the use of tools.

PRINETO Velcro system roll with grid foil



To enable the **PRINETO** Velcro surface heating pipe to be fixed onto the high-quality sound insulation and heat insulation boards, these have Velcro fleece laminated onto their surface. In conjunction with foil overlap on the long sides, adhesive strips ensure the lengths are bonded screed-tight.

Guide eyelet for **PRINETO** pipe reel carrier



The **PRINETO** pipe reel carrier speeds up laying of the surface heating pipes – providing ideal support particularly when laying work is being done by only one person.

Pipe guide for doorways



If the **PRINETO** surface heating is to be laid in adjacent rooms, the special pipe guide makes installation easy.



OUR TIP!

Professional installation glove

The professional installation glove effectively protects hands against injuries that could be caused by the Velcro hook strip of the Velcro surface heating pipe.

Installation of the **PRINETO** Velcro system – fast, efficient, toolless



1.

Roll out the Velcro system roll and fit it in the room



2.

Fix the edge insulation strip to the Velcro system roll using the adhesive strip (or adhesive tape at the ends)



3.

Use the adhesive strip to connect the Velcro system rolls at the foil overlap at the sides



4.

Use the doorway pipe guide to lay the Velcro surface heating pipe from outside the room (optional)



5.

Apply slight pressure to fix the Velcro surface heating pipe to the insulation



6.

For the manifold connection or pipe connections, unwind about 5 cm Velcro tape at the end of the heating pipe and cut this off using a sharp blade

Technical details

PRINETO Velcro surface heating pipe, highly flexible, self-cross-linking

Description	s mm	Weight kg/m	Art. no.	PU
Velcro surface heating pipe, highly flex. 17	2.0	0.104	878 311 551	240
Velcro surface heating pipe, highly flex. 17	2.0	0.104	878 311 552	600
Velcro MLCP heating pipe, Stabil 16x2,0	2,0	0,110	878 311 540	100
Velcro MLCP heating pipe, Stabil 16x2,0	2,0	0,110	878 311 542	400



PRINETO Velcro system roll with grid foil, EPS 30 mm DES

Description	Thickness mm	Width mm	Length m	R m ² K/W	Weight kg/m ²	Art. no.	PU m ²
System roll	30	1,000	10	0.75	0.500	878 386 291	10



PRINETO Velcro guide eyelet

Description	Weight kg/unit	Art. no.	PU
Velcro guide eyelet with adapter	1.100	878 386 072	1



PRINETO Velcro pipe guide for doorways

Description	Weight kg/unit	Art. no.	PU
Velcro pipe guide for doorways	2.000	878 386 075	1



PRINETO Velcro professional installation glove

Description	Weight kg/unit	Art. no.	PU
Velcro professional installation glove	0.050	878 386 076	1



The system that makes laying a pleasure



Toolless laying



Efficiency increased by up to 50 % through one-man laying



Ultra-flexible pipe



Correction possible at all times



Laying time reduced by up to 30 %



Versatile pipe duct



Questions?

Our back-office staff and sales consultants in the field will be happy to help with any queries you may have. Just give us a call:

Tel.: +49 (0) 9876/97 86-0/-42

IVT GmbH & Co. KG
Gewerbering Nord 5
D-91189 Rohr
Tel./Fax. +49 (0) 9876/97 86-42/-90
Info@ivt-group.com • www.ivt-group.com

